

### B.KFX-II 型软管开孔封口旋（拍）盖机

### **B.KFX-II Tube Holing & Sealing &Capping (screwing) Machine**



#### B.KFX-II Tube Holing & Sealing &Capping (screwing) Machine

This machine is suitable for opening the hole in the head of plastic or aluminum-plastic laminated tube which is hermetic, and sealing the hole with aluminum foil, then capping the tube finally. It includes three functions together.

This machine is an ideal machine for the tube manufacture plants. It uses the advanced PLC control and screen-touch interface programs, and the servo electric drive can keeps pinpoint. It also enjoys firm structure, widely usage, high speed and stable operation. Accurate holing, attractive sealing and precise capping are all the advantages of the machine.

#### 主要技术参数（Main Technical Parameters）

电源	Power Supply	380V 50Hz
功率	Power	3.5kw
气源	Air Supply	0.5MPa
耗气量	Air Consumption	0.8m <sup>3</sup> /min
生产能力	Productivity	55 pcs/min
贴膜合格率	Foiling Precision	99%
拧盖合格率	Capping Precision	99%
适用管径	Tube Diameter	Φ 19~Φ 50mm
铝箔厚度	Thickness of Aluminum Foil	0.008~0.01mm
外形尺寸	Dimension(L×W×H)	2200×2000×1800
整机重量	Weight	850kg